

2 Mil White Non-Top Coated
Polyester / SP-705 / 6 mil Layflat

FACESTOCK DESCRIPTION: 2 Mil White Non-Top Coated Polyester

A white film with high opacity, high strength, and good dimensional stability. Also features a unique glossy appearance. This product is suitable for thermal transfer printing as well as flexo printing.

Caliper, mils	2.0
Yield, sq. in/lb	9,825
Gloss 60°, %	45
Tensile, MD / TD, psi	22,000 / 23,000
Ultimate Elongation, MD, %	115 / 90
Shrinkage, (374°F/5 min) MD / TD, %	2.8 / 1.0
Regulatory Compliances	Acute Oral Toxicity 16 CFR 1500.3, ASTM F963 Child Toy Safety, Primary Skin Irritant 16 CFR 1500.41, RoHS

ADHESIVE DESCRIPTION: SP-705

An aggressive emulsion acrylic adhesive with excellent water resistance, high shear, and great performance on PVC. Designed with good die-cutting, stripping, and trimming properties. This adhesive is suitable for mandrel applications.

Type	General Purpose Permanent
Classification	Emulsion Acrylic
Minimum Application Temp., °F	+25
Service Temperature Range, °F	-40 to +176
Regulatory Compliances	California Proposition 65, CONEG, FDA 21 CFR 175.105, Natural Rubber Latex Free, REACH, RoHS

LINER DESCRIPTION: 6 Mil Layflat

A clay-coated kraft liner. Recommended for roll-to-sheet or roll-to-fanfold applications.

Basis Weight (25 x 38 / 500), lbs.	88.5
Caliper, mils	6.2
Gloss, 75°, %	18
Tear, MD / CD, g	90 / 108
Tensile, MD / CD, lbs.	46 / 19
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, CPSIA, REACH, RoHS

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.